

MARBLE PAINT

Product No. **EF 982**

Special effect single component Marble paint based on special Polyurethane varnish, obtained by a unique method of application of selected stains and a choice of intermediate colour contrast .

USES

It is recommended for all type of woodworks, kitchen, internal doors and frames, head boards and drawers.

Area to use: Interior

CHARACTERISTICS

Properties

- Good Flexibility
- Good Hardness
- Marble effect

Color : 13 Different colors.
Specific gravity : 0.95 Kg/lit [± 0.025]

Weight Solids : 5% [± 1]
Flash point : 21°C

Drying Time
Over Spraying : 15 min. at 25°C

Drying time for these stains depends on the type of application and no guidelines can be given.

SURFACE PREPARATION

All timber species must be fully aged with a moisture content of less than 15%. Surface must be dry, clean and free from contaminations. Natural oil or gum must be removed by solvent cleaning.

- Surface must be primed by either polyurethane or polyester primer.
- Sand with sandpaper and apply one coat of PU pigmented Matt and let it dry for about 24 hrs.

PRODUCT PREPARATION

Stir product well with a flat paddle. For details of spray equipment contact Ritver Technical Services Department.

Dilution

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: April 28, 2019

MARBLE PAINT

Product No. **EF 982**

These special stains can be diluted with, NC thinner, PU thinner, water, acetone. The dilution varies from 100% to 500%, and it is related to the design and concentration required

NB: It is not suggested to dilute the product with white spirit.

APPLICATION METHODS

Depends on the finishes required but in general an appropriate rate is 12 sq. m./l. The number of coats depends on the surface preparation the porosity of the substrate, and the finish required.

Following Treatments

These special stains can be applied by hand-held or on-line spray guns, with running spray guns, and keep it for 5 minutes before patching with a cloth or sponge soaked with acetone to obtained a MARBLE EFFECT.

CLEANING

Cleaning

Clean all tools and equipment immediately after use with [TC010] Tool Cleaning.

PACKING & STORAGE

Available in 1USG, 5USG.

Store in a cool and well ventilated place. Keep away from direct sunlight. 18 months in unopened container, stored in a cool and dry condition at 25°C.

SAFETY & FLAMMABLE

This material is flammable and must not be exposed to naked flames.

Use only in well ventilated areas. In case of insufficient ventilation during application wear suitable respiratory equipment. Do not breathe vapor / spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. In case of contact with skin, wash immediately with soap and water or a recognized skin cleanser.

Keep away from sources of ignition. No Smoking. Keep out of reach of children.