

MULTI COLOR PAINT

Product No. **EF985**

Ritver Multi Color Paint is a two component based on acrylic resin with bright metallic sparkle glittery with an attractive looking effect. It gives coloristic effect according to the color of the substrate. The product is particularly recommended when a bright metallic luster is desired.

USE

Substrates: Woodworks, kitchen, internal door and frames, head board and drawers.
Area of Use: Interior

SPECIFICATIONS

Properties

Finish	: Glossy
Colour	: Multi color
Specific gravity	: 0.97 ± 0.02
Solids by weight	: $38 \pm 2.0 \%$
Diluent	: TP222
Flash point	: 21°C
Application Rate	: 100 gr/m ² (per coat)
Drying Time (25°C)	
Dust Free	: 15 minutes
Touch Drying	: 25 minutes
Deep Drying	: 24 hours
Packing	: 48 hours
Recommended DFT	: 10-15 microns

SURFACE PREPARATION

All timber species must be fully aged with a moisture content of less than 15%. Surface must be dry, clean and free from contaminations. Natural oil or gum must be removed by solvent cleaning.

It can be used on veneer substrate, solid wood, and MDF which were treated with pigmented polyurethane or polyester basecoats. Apply two or more coats according to the desired covering. After drying, sand the basecoat with at least 400 type sanding paper. Ensure that no residues on the substrate before application of topcoat.

APPLICATION METHODS

Depends on the finishes required but in general an appropriate rate is 100gr.m². The number of coats depends on the surface preparation the porosity of the substrate, and the finish required.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

MULTI COLOR PAINT

Product No. **EF985**

APPLICATION METHODS

Use spray gun with a 1.8 – 2.0 mm. nozzle at 3-4 atm/bar.
 NB: Application over pigmented basecoats or pigmented matt topcoats (dark colours) creates a glittering metallic effect that is more pronounced than that produced by (metal finish effect).
 After drying this product does not need particular subsequent treatment.
 Anyway, it is possible to apply on top of Multicolor Paint (After 2hours without sanding) an acrylic top finish glossy (to increase the brightness) or matt (for a matt effect).

TYPICAL PAINT SYSTEM

Ritver Multi Color Paint Or as per Ritver technical advice	Ritver PU Primer Black Ritver Multi Color Paint Ritver Acrylic Topcoat	2 coats 2 coats 1 coat
--	---	-------------------------------------

STORAGE & SHELF LIFE

Under dry and cool condition, Storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: 21°C.

Caution: It is strongly advised not to keep open half used drums as it forms a skin on the top layer.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.