

THINNER

Product Code: **PT6001**

Thinner PT6001 is a mixture of Aromatic solvents, Glycol Ether Esters. The product has very good solvency of different resins systems making it very suitable in different paint systems like Thermoplastic Acrylics, Chlorinated Rubber Paints, 2K Acrylics and epoxies.

SPECIFICATION

Properties

Colour	: Clear Transparent
Specific gravity	: 0.902 ± 0.02
Flash point	: 27°C

APPLICATION METHODS

Thinner PT6001 is added to reduce the viscosity of the paint to aid in the proper application of the coating.

Caution: While excess usage / over thinning is not advisable in any system, one can add 5 - 10% of the concerned Thinner for ease of application of brush/roller/or spray viscosity.

STORAGE & SHELF LIFE

Under dry and cool condition, Storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.