

GLOSS EMULSION

Product No. **PW3751**

Ritver Gloss Emulsion is a luxury range emulsion paint specially formulated with a special acrylic emulsion with copious amounts of titanium dioxide and other carefully selected ingredients. It gives long life to the coatings and has good gloss and gloss retention properties and can withstand the rigors of the gulf climatic conditions. Ritver Gloss Emulsion has all the good virtues like hiding, good flow, good wash ability, and superior scrub resistance, smooth finish. **[This product is certified by Dubai Central Laboratory following DM-DLCD-RD-DP21-2180-(IC) Specific Rules for Low Emitting Materials as per the 2017 Al Sa'fat Dubai Green Building Evaluation System.]**

USE

Substrates: Concrete, cement plaster, masonry, gypsum, block work etc.

Area of Use: Interiors/Exterior

SPECIFICATIONS

Properties

Finish	: Smooth & Gloss
Color	: White + all shades as per Ritver shade card and custom made
Specific gravity	: 1.20 ± 0.02
Solids (% by volume)	: 35 ± 1
Diluent	: Sweet Water
Flash point	: Not Applicable
Spread Rate:	

While the spread rate is directly dependent on the surface profile and also the type of undulations it has, by roller and also the equipment they used, **Ritver Gloss Emulsion** it would cover app 9 - 10 m² / liter at 40-50 microns per coat.

Drying Time (30°C)	: Set to touch: 1 ½ - 2 hours.
	: Ready for Recoat: app 3 - 4 hours.
Recommended DFT	: 2 coats. App 40 - 50 mic per coat.

SURFACE PREPARATION

A good surface preparation and following the method statement / recommended system procedure of Ritver is an ideal recommendation for the application of **Ritver Gloss Emulsion**.

For Plaster, Masonry & Concrete:

Achieve a good and clean surface by removing all contaminants and loose particles by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Water washing under pressure is recommended. Apply the Ritver All Acrylic primer or Ritver All weather Tex Primer and allow drying as per the data sheet and subject to one more coat for even coverage. After applying the primer, apply a uniform layer of Ritver Stucco Putty/Ritver filler compound, follow it up with Ritver Platinum one coat and make a couple of coats of Ritver Gloss Emulsion. It is always advisable to go through Ritver Platinum Emulsion (one coat) in case it is difficult to coat over Ritver Stucco Putty due to heavy loading of the putty.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: May 26, 2019

GLOSS EMULSION

Product No. **PW3751**

For Old and Painted surfaces:

In case of surfaces which are painted / or aged and if there is visible dusting, chalking or even friable, ensure that all the loose material is removed by scrapping or metal brush. Apply a good coat Ritver Fungicidal wash compound and allow drying. Follow this by a regular coat or two of Ritver All Acrylic Primer or Ritver All Weather Tex Primer and continue as in the above case with the full system.

APPLICATION METHODS

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

1. **Dilution:** One can add 5 to 10% of sweet water for ease of application depending on the suitability of application.
2. **Brush:** It is in ideal recommendation especially to avoid runs and sags due to excess.
3. **Roller:** Apply an even coat spreading uniformly taking care to avoid runs.
4. **Airless spray:** Use tip size around 0.018" to 0.020" and pressure around 2000. – 2500 psi.

Ritver Gloss Emulsion

Recommended system to be applied as per surface preparation.

Or as per Ritver technical advice

Ritver PVA Primer
Ritver Stucco Putty
Ritver Gloss Emulsion

1 coat
2 coats
2 coats

STORAGE AND SHELF LIFE

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: May 26, 2019