

## BLAZEBAR MATT FINISH

Product No. **PW3304**

**Blazebar Matt Finish** is a water based Fire Retardant paint formulated with advanced raw materials that provide a non-flaming paint surface when exposed to extreme heat. Unlike ordinary acrylic based systems, this product does not aid in the propagation of fire by extinguishing itself when exposed to flame. It is an effective fire retardant wall paint. The product can be used as a primer when diluted to penetrate the substrate, and as a luxury matt finish topcoat in interior and exterior applications. The product can also be used in ETICS systems. **This product is certified by Thomas Bell-Wright following the Multi-coat Interior Finish Systems for Reaction to Fire performance according to test standard ASTM E84-19a and approved by DCD under license no. LMTNA0000135842-2019.**

### USE

**Substrates:** Concrete, Metal, Wood  
**Area of Use:** Exterior & Interior

### SPECIFICATIONS

#### Properties

<b>Finish</b>	: Matt and Satin
<b>Colour</b>	: White and Pastels
<b>Specific gravity</b>	: 1.45 ± 0.05
<b>Solids (% by vol.)</b>	: 35 ± 2%
<b>Diluent</b>	: Water
<b>Flash point</b>	: N/A
<b>Spread Rate</b>	: 8.75 sq.m./liter
<b>Recommended DFT</b>	: 40 microns/coat
<b>Drying Time, 30° C @ 50%RH</b>	
<b>Touch Dry</b>	: 1 hours
<b>Dry to Recoat</b>	: 2 hours
<b>Hard Dry</b>	: 6 hours

### SURFACE PREPARATION

#### Concrete

Always ensure that the surface to be painted must be free of dirt oil and grease. New concrete should be cured for at least 28 days before application. Old painted surfaces should be removed of old paints and primed with **Blazebar Matt Finish**. Ensure that all old paints are removed.

#### Metal

Bare metal should be cleaned according to SSPC SP2 (Handtool Cleaning) or SSPC SP3 (Power Tool Cleaning) and primed with a suitable primer. Ensure primer is fully cured before application of **Blazebar Matt Finish**.

#### Wood

If applying over coated wood, ensure that the coating is compatible with **Blazebar Matt Finish**.

**NOTE: For any Flame Retardant system to be successful, it is imperative that all previous coatings are stable and firmly adhering to the substrate.**

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: Dec. 05, 2017

## BLAZEBAR MATT FINISH

Product No. **PW3304**

### APPLICATION METHODS

The recommended method of application is by Airless Spray. Roller or Brush.

#### Application:

Mix the product properly before application. Thin down with 30% water and apply as the Primer for good penetration. Dilute 5 to 15 % and use as the topcoat.

#### Airless Spray

Depending on the area to be covered, select the most suitable fan type, normally 4 to 8 inches and a nozzle orifice of 0.021 to 0.027 of an inch. Do not apply more than 100 microns wet at a time or the product will sag and crack. Wait until the first coat is dried before commencing with the next coat. Build the dry film thickness to 80 microns minimum by applying multiple coats.

#### Roller/Brush

Apply the product using a fine haired paint roller or brush, the one usually used for Emulsion Paints. Apply multiple coats to build the recommended DFT.

### STORAGE & SHELF LIFE

Under dry and cool condition, Storage stability can be sound up to 18 months in original sealed containers.

#### HANDLING

**Disposal:** As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

### SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

#### FIRST AID

**Eyes:** In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

**Skin:** Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

**Inhalation:** Remove to fresh air, loosen collar and keep patient rested.

**Ingestion:** In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.