

GLOSSY TEXTURE Product No. PW3721

Ritver Glossy Texture is a copolymer based composition designed to be applied by appropriate roller and spreading into different patterns and is an integral part of the Ritver Texture system. Ritver Glossy texture emulsion contains special grades of pigments with copious amounts of a superior grade of emulsion and has good colour retention and weather ability. Its film is quite flexible and covers up the unevenness of the surface. It has got good antibacterial and anti fungal properties.

USE

Substates: Concrete, plaster, masonry, portable cabins and false ceilings.

Area of Use: Interiors & Exteriors.

SPECIFICATIONS

Properties

Finish	: Glossy and regular texture.
Colour	: Off white and selected colours
Specific gravity	: $1.36 \pm .02$
Mixed Solids (% by volume)	: $48 \pm 1\%$
Diluent	: Sweet water
Flash point	: Not applicable

Spread Rate:

While the spread rate is directly dependant on the surface profile and also the type of undulations it has, as a thumb rule **Ritver Glossy Texture** would cover 1.5 to 2.0 sq. meters per lit.

Drying Time (30° C)	: Set to touch: 2 – 3 hours. : Ready for Recoat: app 6- 8 hours.
----------------------------	---

Recommended DFT	: 1 mist coat followed by a good top coat. App 150 – 200 mic.
------------------------	---

SURFACE PREPARATION

A good surface preparation and following the method statement / recommended system procedure of Ritver is an ideal recommendation for the application of **Ritver Glossy Texture**.

For Plaster, Masonry & Concrete:

Achieve a good and clean surface by removing all contaminants by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush.

Before applying the **Ritver Glossy Texture** apply one coat of **Ritver Alkali Resistant primer or Ritver all weather Tex primer** and allow drying. Apply one good coat or two nominal coats with the roller and obtain the desired texture.

Exclusions for successful application include perpetually wet surfaces and also large cavities on concrete surfaces.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

GLOSSY TEXTURE Product No. PW3721

APPLICATION METHODS

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

Application: To be done by texture roller to vary the pattern. One can add 5% of sweet water for ease of application depending on the suitability of application even though it is ready to use consistency.

Caution: Over diluting would result in a flat and wrong texture.

TYPICAL PAINT SYSTEM

<p>Recommended system to be applied as per surface preparation.</p> <ul style="list-style-type: none"> Or as per Ritver technical advice 	<p>Ritver All Weather Tex Primer Ritver Glossy Texture</p>	<p>1 coat 2 coats</p>
---	--	---------------------------

STORAGE & SHELF LIFE

Under dry and cool conditions storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.